



Glatte oder Gewinde-Enden		Plain or threaded ends			
Abzweiggröße Outlet size Zoll / Inches	3000 lbs		6000 lbs		
	Abmessungen Dimensions mm		Abmessungen Dimensions mm		
	A	C	A	C	
1/2	90	23,8	90	14,3	
3/4	90	30,2	90	19,0	
1	90	36,5	90	25,0	
1 1/4	90	44,5	90	33,0	
1 1/2	90	50,8	90	38,0	
2	90	65,0	90	43,0	

NIPOLET®

Speziell entwickelt für unterstützungsfreie Armaturenmontage

NIPOLET®

Specially designed for support-free valve installation

Reduktion der Variantenvielfalt durch intelligente Konstruktion

Eine Weldolet-Größe passt auf mehrere Grundrohrgrößen (gilt auch für Thredolet®, Nipolet®, Elbolet®, Latrolet® und Sockolet®)

Reduction of varieties through intelligent construction

A Weldolet size is suitable for various run pipe sizes (applicable also for Thredolet®, Nipolet®, Elbolet®, Latrolet® and Sockolet®)

Tabelle gültig für Weldolet® (Standard und Extra Strong), Thredolet® (3000 lbs) und Sockolet® (3000 lbs)
 Table valid for Weldolet® (Standard and Extra Strong), Thredolet® (3000 lbs) and Sockolet® (3000 lbs)

Zoll Inches	passend für Grundrohrgröße suitable for run pipe									
1/8	3/8	1/2	1-3/4	2 1/2-1 1/4	36-3					
1/4	3/8	1/2	1-3/4	2 1/2-1 1/4	36-3					
3/8	1/2	1-3/4	2 1/2-1 1/4	36-3						
1/2	1/2	3/4	1	1 1/2-1 1/4	2 1/2-2	8-3	36-10			
3/4	3/4	1	1 1/2-1 1/4	2 1/2-2	5-3	12-6	36-14			
1	1	1 1/4	1 1/2	2	2 1/2	3 1/2-3	5-4	10-6	36-12	
1 1/4	1 1/4	1 1/2	2	2 1/2	3 1/2-3	5-4	8-6	18-10	36-20	
1 1/2	1 1/2	2	2 1/2	3	4-3 1/2	6-5	12-8	24-14	36-26	
2	2	2 1/2	3	3 1/2	4	5	6	10-8	18-12	36-20
2 1/2	2 1/2	3	3 1/2	4	5	6	8	12-10	18-14	36-20
3	3	3 1/2	4	5	6	8	10	14-12	20-16	36-24
3 1/2	3 1/2	4	5	6	8	10	14-12	20-16	36-24	
4	4	5	6	8	10	14-12	20-16	36-24		

Tabelle gültig für Thredolet® (6000 lbs) und Sockolet® (6000 lbs)
 Table valid for Thredolet® (6000 lbs) and Sockolet® (6000 lbs)

Zoll Inches	passend für Grundrohrgröße suitable for run pipe							
1/2	1-3/4	2-1 1/4	6-2 1/2	36-8				
3/4	1	2 1/2-1 1/4	10-3	36-12				
1	1 1/2-1 1/4	2 1/2-2	10-3	36-12				
1 1/4	1 1/2	2 1/2-2	3 1/2-3	8-4	20-10	36-24		
1 1/2	2	2 1/2	3 1/2-3	5-4	8-6	18-10	36-20	
2	2 1/2	3	4	5	6	10-8	20-12	36-24

Tabelle gültig für Weldolet® (Schedule 160 & XXS)
 Table valid for Weldolet® (Schedule 160 & XXS)

Zoll Inches	passend für Grundrohrgröße suitable for run pipe							
1/2	1 1/4-3/4	36-1 1/2						
3/4	1-3/4	2-1 1/4	6-2 1/2	36-8				
1	2 1/2-1 1/4	10-3	36-12					
1 1/4	1 1/2-1 1/4	2 1/2-2	10-3	36-12				
1 1/2	2	2 1/2	3 1/2-3	8-4	20-10	36-24		
2	2 1/2	3	4	5	6	10-8	20-12	36-24