











Gewinde-Fittings nach ANSI B 16.11

Threaded-Fittings according to ANSI B 16.11

Zoll / Inches		1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"		
DN		mm	8	10	15	20	25	32	40	50	65	80	100	
Muffen Couplings		3000 lbs	D	19	22,2	28,5	35	44,5	57,5	63,5	77	92	108	140
			W	35	38	48	51	60	66,5	80	86	92	108	120
		6000 lbs	D	26	32	38	44,5	57,5	63,5	77	92	108	127	
			W	35	38	48	51	60	66,5	80	86	92	108	
Halbe Muffen Half Couplings		3000 lbs	D	19	22,2	28,5	35	44,5	57,5	63,5	77	92	108	140
			W/2	17,5	19	24	25,5	30	33	40	43	46	54	60
		6000 lbs	D	26	32	38	44,5	57,5	63,5	77	92	108	127	
			W/2	17,5	19	24	25,5	30	33	40	43	46	54	
Reduzierte Muffen Reducing Couplings		3000 lbs	D	19	22,2	28,5	35	44,5	57,5	63,5	77	92	108	140
			W	35	38	48	51	60	66,5	80	86	92	108	120
		6000 lbs	D	26	32	38	44,5	57,5	63,5	77	92	108	127	
			W	35	38	48	51	60	66,5	80	86	92	108	
90° Winkel 90° Elbows		3000 lbs	H	25	33	38	46	56	62	76	86	102	120	152
			A	24	28	34	38	44	50	60	64	82	95	114
		6000 lbs	H	33	38	46	56	62	76	86	102	120	146	152
			A	28	34	38	44	50	60	64	82	95	106	114
45° Winkel 45° Elbows		3000 lbs	H	25	33	38	46	56	62	76	86	102	120	152
			A	19	22	25	28,5	34	35	43	44	52	64	80
		6000 lbs	H	33	38	46	56	62	76	86	102	120	152	152
			A	22	25	28,5	34	35	43	44	52	64	80	80
T-Stücke u. Red. T-Stücke Tees: Equal and Reducing		3000 lbs	H	25	33	38	46	56	62	76	86	102	120	152
			A	24	28	34	38	44	50	60	64	82	95	114
		6000 lbs	H	33	38	46	56	62	76	86	102	120	146	152
			A	28	34	38	44	50	60	64	82	95	106	114
Kreuzstücke Crosses		3000 lbs	H	25	33	38	46	56	62	76	86	102	120	152
			A	24	28	34	38	44	50	60	64	82	95	114
		6000 lbs	H	33	38	46	56	62	76	86	102	120	152	
			A	28	34	38	44	50	60	64	82	95	114	
Verschraubungen I/I Unions F/F		3000 lbs	R	36	41	46	56	65	80	88	105	122	144	180
			Q	42,5	47,5	52	57	63	70	78	89	120	140	150
		6000 lbs	R	46	51	60	72	80	94	100	122	144	180	
			Q	54	57	69	72	80	89	108	114	130	150	
Verschraubungen A/I Unions M/F		3000 lbs	R	36	41	46	56	65	80	88	105			
			Q	61	69	75	80	90	98	105	120			
		6000 lbs	R	46	51	60	72	80	94	100	122			
			Q	72,5	77	94,5	98,5	108	120	138	146			
90° Winkel A/I 90° Street Elbows M/F		3000 lbs	N	32	37,5	41,5	47,5	57	66,5	71,5	84,5			
			M	24,5	29	33,5	38	44,5	51	57,5	63,5			

Zoll / Inches	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"		
DN	mm	8	10	15	20	25	32	40	50	65	80	100	
90° Winkelverschraubungen A/I auch mit I/I möglich 90° Union Elbows M/F also possible F/F 	3000 lbs	M			38	38	44,5	60,5	60,5	63,5			
		P			88	90	108	126	132	140			
Reduzierstück A/I Bushings M/F 	3000 lbs / 6000 lbs	F	16	17,5	22	27	35	44,5	51	63,5	76	89	117,5
		A	11	12,5	14,5	16	19	20,5	20,5	22	27	28,5	32
		G	3	4	5	6	6	7	8	9	10	10	13
Kappen Caps 	3000 lbs	D	19	22,2	28,5	35	44,5	57,5	63,5	77	92	108	140
	6000 lbs	P	26	26	32	36	42	45	45	48	60	65	68
		D	26	32	38	44,5	57,5	63,5	77	92	108	127	
		P	27	27	34	38	43	46	48	51	64	68	
Sechskantstopfen Hex. Head Plugs 	3000 lbs / 6000 lbs	F	16	17,5	22	27	35	44,5	51	63,5	76	89	117,5
		A	11	12,5	14,5	16	19	20,5	20,5	22	27	28,5	32
		H	6	8	8	10	10	14	16	17	19	21	25
Vierkantstopfen Square Head Plugs 	3000 lbs / 6000 lbs	C	10	12	14	16	21	24	29	35	38	43	64
		A	23	24	28	31	36	39	41	44	51	55	58
Rundstopfen Round Head Plugs 	3000 lbs / 6000 lbs	D	13,5	17,5	21,4	27	33,3	42,8	48,4	60,3	73	88,9	114,3
		A	42	42	45	45	51	51	51	64	70	70	76
Sechskantnippel Hexagonal Nipples 	3000 lbs / 6000 lbs	A	16	17,5	22	27	35	44,5	50	63,5	76	89	117,5
		W	39	40	46	51	57	65	66	70	84	90	104
Reduzierte Sechskantnippel A/A Red. Hex. Nipples M/M 	3000 lbs / 6000 lbs	A	16	17,5	22	27	35	44,5	50	63,5	76	89	117,5
Schweißstützen 1x mit Gewinde Weld BOSS NPT 	3000 lbs / 6000 lbs	K	30,5	30,5	33,5	35,0	43,0	48,0	51,0	57,5			
		M	28,0	32,0	38,0	44,5	57,5	63,5	76,0	92,0			
		N	14,0	17,4	21,6	26,9	33,6	42,4	48,5	60,9			
Reduzierstücke I/A Reducer F/M 	3000 lbs / 6000 lbs	K		42	49	59	63	68	72	75	92	95	113
		M		22	28	35	45	60	65	76	95	110	140